

IN THE SPECIFICATION:

Kindly amend the specification as follows:

Please amend Paragraph [0014] as follows:

A1 [0014] Figure 2 is an enlarged cross-sectional schematic front view taken along lines II-II of a detail of the crawler vehicle of Figure 1, but depicted in different operating positions depicting the relative positions of the cross members 18 as the vehicle moves across level and rough terrain;

Please amend Paragraph [0017] as follows:

A2 [0017] Figure 6 is a partial side view of a variation of the connecting assembly 25 of the crawler vehicle depicted in Figures 1 – 5 with a track carriage in two different operating positions.

Please amend Paragraph [0023] as follows:

A3 [0023] With particular reference to Figures 3 to 5, the pin 30 includes two coaxial, opposite cylindrical end portions 36, 37, which engage respective the seats 15 and 16 along the axis 17 in axially-fixed, rotary manner to permit relative oscillation of the cross member 18 and each carriage 4 from the neutral position shown in solid line between the phantom positions, as seen in Figure 3. The pin 30 further includes a cylindrical intermediate portion 38, which extends between the end portions 36 and 37 along with a respective axis 40 parallel to and offset with respect to the axis 17. The portion 38 has a diameter having a size between those of portions 36, 37, and has two diametrically opposite generating lines defining extensions of a respective upper generating line of the portion 36 and a lower generating line of portion 37, with respect to the view of Figure 4.